


开关外形尺寸:



开关技术特性(Switch technical Characteristics):

项目 (ITEM)	技术参数 (technical parameter)	特性值 (Value)
1	电气额定值 (Electrical Rating)	E(2)A/10A/16(3)A/21(8)A 250VAC
2	接触电阻 (Contact Resistance)	≤30mΩ (初始值 Initial value)
3	绝缘电阻 (Insulation Resistance)	≥100MΩ (500VDC)
4	耐压强度 (Dielectric Voltage)	同极不相接端子间 (between non-connected terminals)
		端子与外壳或非载流金属零件之间 (between terminals and the metal frame)
5	电气寿命 (Electrical Life)	1000V/0.5mA/6CS
6	机械寿命 (Mechanical Life)	≥50000 cycles
7	工作温度 (Operating Temperature)	≥1000000 cycles
8	操作频率 (Operating Frequency)	-25~125℃
9	抗震动 (Vibration Proof)	电气 (electrical) :15 cycles
		机械 (Mechanical) :60 cycles
10	可焊性 (Solder Ability): 超过 80% 的浸锡面积被焊料所覆盖 (More than 80% of immersed part shall be covered with solder)	振动频率 (Vibration Frequency): 10~55HZ;
		振幅 (Amplitude): 1.5mm;
11	耐焊接热 (Solder Heat Resistance)	三向 (Three directions) :1H
		焊接温度 (Soldering Temperature): 235±5℃
12	安全认证 (Safety Approvals)	浸锡时间 (Immersing Time): 2~3S
		自动焊接 (Dip Soldering): 260±5℃ 5±1S
13	测试条件 (Test Conditions)	手工焊接 (Manual Soldering): 300±5℃ 2~3S
		环境温度 (Ambient Temperature): 20±5℃
		相对湿度 (Relative Humidity): 65±5%RH
		大气压 (Air Pressure): 86~106KPa

NO.	PARTS	MATERIALS	Q'TY		TOLERANCE UNLESS SPECIFIED				
8					WITHIN 1.5mm : ±0.1mm	A	2012-8-13	初版	
7					OVER 1.5mm : ±0.2mm	ISSUE	DATE	DESCRIPTIONS OF REVISION	
6								APPD.	
5	SPRING	SUS	1	NATURAL	TITLE : Micro Switch			UNIT : mm	DRWG NO.:
4	CAM STICK	SUS	1	NATURAL	MODEL:			SCALE: 5:1	DWN.
3	CASE	PA66/BRASS STRIP	1	GREY/Ag PLATED	 <b>广东科斯达开关厂</b>				2012-8-13
2	COVER	PA66	1	BLACK				CHK'D	
1	KNOB	PA66/PBS C5210R-EH	1	WHITE/Ag CLAD	APPD.				