





RoHS

REV	ECN NO	DESCRIPTION	DATE	NAME
A		NEW		



PCB LAYOUT

- ### Specifications
- 1.Current Rating:2.0Amps
 - 2.Insulation Resistance:1000 MΩ min.
 - 3.Dielectric withstanding Voltage: 500V AC/DC
 - 4.Contact Resistance:20 mΩ max.
 - 5.Operating Temperature:-40℃ to+105℃
 - 6.Contact Material: Brass
 - 7.Insulation Material:As follows,UL94V-0,Black
 - 8.Plated: Au Over Ni

Ordering Information

Insulation Height*Wide (H*W)	NO. of Pins Per Row: 1-50P	Insulation Material Option:	Contact Plating	Serial NO.	Packing
10=1.0*2.0 15=1.5*2.3 40=4.0*4.3		1=PBT 2=PPS 3=NY6T 4=LCP 5=NY66 6=Customized 7=NY46 8=NY9T	0=0.8" Gold 1=Au1" Gold 2=Au1.5" Gold 3=Au2" Gold 4=Au3" Gold 5=Au5" Gold 6=Customized 7=Gold/Tin 8=Tin	01-69	A=PE Bag B=Tube C=Tray D=Reel

ITEM	PC	PA	H	Pin Length
Standard	2.80	4.00	4.00	10.6/14.6
Alternate				

广东科斯达电子科技有限公司

STANDARD TOLERANCE (EXCEPT SPECIFIED)			
LINER		ANGLES	
.0	±0.30	0.°	±3°
.00	±0.20	.0°	±2°
.000	±0.10	.00°	±1°

TITLE	PH2.00mm Pin Header Dual Row 90°	DRAWN BY	YTT	16.02.03
PART NO		CHECKED BY		
DRAWING NO		APPROVED BY		
SCALE	1:1	UNITE	mm	PAGE 1/1
				SIZE A4