

RoHS

REV	ECN NO	DESCRIPTION	DATE	NAME
A		NEW		




Specifications

- 1.Current Rating:1.0Amps
- 2.Insulation Resistance:1000 MΩ min.
- 3.Dielectric withstanding Voltage: 500V AC/DC
- 4.Contact Resistance:20 mΩ max.
- 5.Operating Temperature:-40°C to+105°C
- 6.Contact Material: Brass
- 7.Insulation Material:As follows,UL94V-0,Black
- 8.Plated: Au Over Ni

Ordering Information

Insulation Height*Wide (H*W)	NO. of Pins Per Row:	Insulation Material	Contact Plating	Serial NO. 01-69	Packing
Option: 10=1.0*2.0 15=1.5*2.3 15=1.5*3.2	1-50P	Option: 1=PBT 2=PPS 3=NY6T 4=LCP 5=NY66 6=Customized 7=NY46 8=NY9T	0=0.8" Gold 1=Au1" Gold 2=Au1.5" Gold 3=Au2" Gold 4=Au3" Gold 5=Au5" Gold 6=Customized 7=Gold/Tin 8=Tin		A=PE Bag B=Tube C=Tray D=Reel

ITEM	PC	PA	H	Pin Length
Standard	2.40	3.00	1.00	6.40
Alternate				



PCB LAYOUT

STANDARD TOLERANCE (EXCEPT SPECIFIED)	
LINER	ANGLES
.0 ±0.30	0.° ±3°
.00 ±0.20	.0° ±2°
.000 ±0.10	.00° ±1°

广东科斯达开关厂

TITLE	PH1.27mm Pin Header Single Row 180°	DRAWN BY	YTT	16.02.03
PART NO		CHECKED BY		
DRAWING NO		APPROVED BY		
SCALE	1:1	UNIT	mm	PAGE 1/1
				SIZE A4