



REV.	ECN.NO.	MODIFY.CONTENT	DATE
A		FIRST VERSION	2/23' 21

技术参数 Main Specifications

极数 CKT: 4 ~ 40

工作温度 Working Temperature: -25°C ~ +85°C

额定电压 Voltage rating(max): 50V, AC/DC

接触电阻 Contact resistance: $\leq 0.03\Omega$

绝缘电阻 Insulation resistance: $\geq 500M\Omega$

额定电流 Current rating: 0.5A

耐电压 Withstand voltage: 500VAC(rms)

材料 Material

接触端子 Terminal: 铜合金 Copper alloy

塑胶本体 Housing: UL 94V-0 LCP

CKT	尺寸 Size(mm)		
	A	B	C
4	1.50	2.60	4.00
6	2.50	3.60	5.00
8	3.50	4.60	6.00
10	4.50	5.60	7.00
12	5.50	6.60	8.00
16	7.50	8.60	10.00
20	9.50	9.60	12.00
22	10.50	10.60	13.00
24	11.50	12.60	14.00
30	14.50	15.60	17.00
40	19.50	20.60	22.00

GENERAL TOLERANCE		DRAWN	Wilson Sun	02/23'21	SCALE	PART NO.	
X.±0.30	x.'±3.0'	CHECKED	SHENGJIE CHU	02/23'21	1/1	TITLE	0.5 Pitch H=1.5 Auto-Lock FPC
.X±0.25	.x'±2.0'	APPROVED	CUNFA LAI	02/23'21	UNITS	mm	CUSTOMER DRAWING
.XX±0.20		File NO.					
.XXX±0.10		REV.					
SHEET	1/3	Q'TY	1	A			

广东科斯达开关厂