



REV.	ECN.NO.	MODIFY.CONTENT	DATE
A		FIRST VERSION	2/23' 21

### 技术参数 Main Specifications

极数 CKT: 4 ~ 50  
 工作温度 Working Temperature:  $-30^{\circ}\text{C} \sim +85^{\circ}\text{C}$   
 额定电压 Voltage rating(max): 50V, AC/DC  
 接触电阻 Contact resistance:  $\leq 30\text{m}\Omega$   
 绝缘电阻 Insulation resistance:  $> 500\text{M}\Omega$   
 额定电流 Current rating: 0.5A  
 耐电压 Withstand voltage: 500VAC(rms)

### 材料 Material

接触端子 Terminal: 铜合金 Copper alloy  
 塑胶本体 Housing: UL 94V-0 LCP

CKT	尺寸 Size(mm)		
	A	B	C
4	1.50	2.60	3.80
6	2.50	3.60	4.80
8	3.50	4.60	5.80
10	4.50	5.60	6.80
12	5.50	6.60	7.80
16	7.50	8.60	9.80
20	9.50	9.60	10.80
22	10.50	10.60	11.80
24	11.50	12.60	13.80
30	14.50	15.60	16.80
40	19.50	20.60	21.80

GENERAL TOLERANCE		DRAWN	Wilson Sun	02/23'21	SCALE	PART NO.	
$X \pm 0.30$	$x' \pm 3.0'$	CHECKED	SHENGJIE CHU	02/23'21	1/1	TITLE	0.5 Pitch H=1.5 Auto-Lock FPC
$.X \pm 0.25$	$.x' \pm 2.0'$	APPROVED	CUNFA LAI	02/23'21	UNITS	mm	CUSTOMER DRAWING
$.XX \pm 0.20$		File NO.					
$.XXX \pm 0.10$		REV.					
SHEET	1/3	QTY	1	A			
<h1>广东科斯达开关厂</h1>							

此文件为双方检验的唯一标准  
 This document is the only standard for inspection by both parties.