



性能:

额定电流: 1A

额定电压: 100V

耐电压: 500V

接触电阻:  $\leq 20\text{m}\Omega$

绝缘电阻:  $500\text{M}\Omega$

工作温度:  $-20^{\circ}\text{C} \sim +85^{\circ}\text{C}$

塑件(材质): LCP, UL94V-0

插簧(材质): 磷青铜, 镀锡/镀金

焊片(材质): 磷青铜, 镀锡/镀金

孔位	A	B	E
2	1.25	7.25	3.05
3	2.50	8.50	4.30
4	3.75	9.75	5.55
5	5.00	11.00	6.80
6	6.25	12.25	8.05
7	7.50	13.50	9.30
8	8.75	14.75	10.55
9	10.00	16.00	11.80
10	11.25	17.25	13.05
11	12.50	18.50	14.30
12	13.75	19.75	15.55
13	15.00	21.00	16.80
14	16.25	22.25	18.05
15	17.50	23.50	19.30
16	18.75	24.75	20.55

X. ± 0.3	X° ± 5°	UNITS mm
.X ± 0.25	.X° ± 2°	MAT'L
.XX ± 0.20	.XX° ± 1°	FINISH
.XXX ± 0.10	.XXX° ± 0.5°	
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DE RUI ELECTRON FACTORY AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF DE RUI ELECTRON FACTORY		Q' TY

**科斯达电子科技有限公司**

PART NO. (INTENDED USE)

TITLE:

1.25mm (D型) 条形连接器卧贴式

APPD:

DWG NO.:

CHKD:

DR: YLZ 2011.09.28



SCALE	SHEET	REV.
1/1	1/1	A