



Receptacle+ Header

# Specifications:

Housing: LCP UL94-V0 Color: Nature

Contact: Phosphor Bronze

Operating Voltage: 250V AC/DC

Current Rating: 2A AC/DC

Withstand Voltage: 800V AC/Minute

Contact Resistance:  $\leq 20\text{m}\Omega$

Insulation resistance:  $\geq 500\text{m}\Omega$

Operating Temperature:  $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$

PIN	A	B	C
2	2.0	4.75	8.0
3	4.0	6.75	10.0
4	6.0	8.75	12.0
5	8.0	10.75	14.0
6	10.0	12.75	16.0
7	12.0	14.75	18.0
8	14.0	16.75	20.0
9	16.0	18.75	22.0
10	18.0	20.75	24.0
11	20.0	22.75	26.0
12	22.0	24.75	28.0
13	24.0	26.75	30.0
14	26.0	28.75	32.0
15	28.0	30.75	34.0
16	30.0	32.75	36.0

## 科斯达电子科技有限公司

檢驗尺寸標示

SYMBOLS ① ② INDICATE CLASSIFICATION DIMENSION

① MARK IS CRITICAL DIM.

② MARK IS MAJOR DIM.

表面處理 (FINISH)

工程圖號

品名

TITLE

比例 (SCALE)

單位 (UNITS)

制圖 (DR)

'15/5/16

審核 (CHKD)

核准 (APPD)

張數 (SHEET)

1 OF 1

Rigo Lu

SIZE

A4

REV

0

REV	DESCRIPTION	DATE	SIGNATURE
1	修改摘要		
2	修改摘要		