



主要技术参数 Main Specifications

- 线数 (Poles): 02 to 16
- 接触电阻 (Contact resistance): $\leq 20m\Omega$
- 绝缘电阻 (Insulation resistance): $\geq 1000M\Omega$
- 额定电压 (Rated voltage): 250V AC DC
- 额定电流 (Rated current): 3.0A AC DC
- 耐电压 (Withstand Voltage): 1000V AC/minute
- 温度范围 (Temperature Range): $-25\text{ }^{\circ}\text{C} \sim +105\text{ }^{\circ}\text{C}$

C	Solder Tab	2 PCS	Brass	Tin-plated
B	Contacts	n PCS	Brass	Tin-plated
A	HOUSING	1 PCS	LCP	UL 94V-0, COLOR:BEIGE
ITEM	COMPONENT	Q'TY	MATERIAL	FINISH

Circuit	Dimensions (mm)				Circuit	Dimensions (mm)			
	A	B	C	D		A	B	C	D
02	2.50	7.50	10.00	8.20	10	22.50	27.50	30.00	28.20
03	5.00	10.00	12.50	10.70	11	25.00	30.00	32.50	30.70
04	7.50	12.50	15.00	13.20	12	27.50	32.50	35.00	33.20
05	10.00	15.00	17.50	15.70	13	30.00	35.00	37.50	35.70
06	12.50	17.50	20.00	18.20	14	32.50	37.50	40.00	38.20
07	15.00	20.00	22.50	20.70	15	35.00	40.00	42.50	40.70
08	17.50	22.50	25.00	23.20	16	37.50	42.50	45.00	43.20
09	20.00	25.00	27.50	25.70					

UNITS
mm

MAT'L

FINISH

Q'TY
PCS

科斯达电子科技有限公司

PART NO.(INTENDED USE)

TITLE:
XH2.54卧贴针座

APPD:

CHKD:

DR: HU 2016.09.28

DWG NO.:

SCALE	SHEET	REV.
1/1	1/1	A

X.± 0.3	X'± 5'
.X± 0.25	.X'± 2'
.XX± 0.20	.XX'± 1'
.XXX± 0.10	.XXX'± 0.5'