



SPECIFICATIONS:

- 1.ELECTRICAL CHARACTERISTICS:1-1.RATING:DC24V 6A
- 1-2.CONTACT RESISTANCE:30m2MAX.(INITIAL)
- 1-3.DIELECTRIC WTHSTANDING VOLTAGE:500V AC FOR ONE MINUTE
- 1-4.INSULATION RESISTANCE:100MQ MIN. MEASURED BY 500V DC
- 2.MECHANICAL CHARACTERISTICS:
- 2-1.Plug it into the mother socket 3 times INSERTION FORCE:03~3.0 KGF
- 2-2. Plug it into the mother socket 5000 times INSERTION FORCE:03~3.0 KG
- 3.SALT FOG:24 Hours
- 4.FOR REFLOW SOLDERING LEAD-FREE PROCESS
- 5. * REPRESENT CRITICAL DIMENSIONS.

	MATERIAL	PLATING
TERMINAL 1	Phosphor bronze	NI
Fork hook tube	C3604	NI
plastic	PBT	Black

				ANGLAR	±5°		DSND		SCALE: N/A	MODEL TYPE: DC PLUG		
				L ≤ 4	±0.2		DWN		VIEW:	PART NO.: DT-2355525		
				4 < L ≤ 16	±0.3		CHKD		UNIT: mm/in	DWG NO.:		
				16 < L ≤ 63	±0.4		APPD		SIZE: A4			
				L > 63	±0.5	UNSPECIFIED TOLERANCES				WEIGHT	SHEET	REVISION
REVISIONS				DATE	REVISED	APPROVED	KE SI DA ELECTRONIC TECHNOLOGY CO., LTD				1/1	A0
WWW.BODONGKAIGUAN.NET				WWW.CKJACK.COM		WWW.KSDKG.COM						