



- SPECIFICATIONS:
- ELECTRICAL CHARACTERISTICS:
 - RATING: 1.8A(PIN1/5), 0.5A(PIN2/3/4)
 - CONTACT RESISTANCE: 30mΩ MAX.(INITIAL)
 - DIELECTRIC WITHSTANDING VOLTAGE: 300V AC FOR ONE MINUTE.
 - INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500 VDC
 - MECHANICAL CHARACTERISTICS:
 - INSERTION FORCE: 3.6 KGF (MAX)
 - WITHDRAWAL FORCE: 0.8 KGF(Reference)
 - DURABILITY: 10,000 CYCLES
 - WATER PROOFNESS: THIS PRODUCT IS BASED ON IPX7(1m,30min)
 - PLUG INTERFACE DIMENSIONS COMFORM TO USB2.0 SPEC.
 - OVAL RING
 - The amount of low molecular siloxanes(D3-D10)is less than 200ppm
 - Hardness of silicone rubber: 70°
 - FOR REFLOW SOLDERING LEAD-FREE PROCESS.
 - PACKAGING: TAPE & REEL



○				
③	Shell	1	Stainless Steel T=0.25	
②	Contact	5	Copper Alloy T=0.20	
①	Housing	1	HI-TEMP. PLASIC UL 94V-0	BLACK
ITEM	PAPT NAME	QTY	MATERIAL	FINISHING

				ANGLAR	±5°	DSND		SCALE: N/A	MODEL TYPE: MICRO USB			
				L ≤ 4	±0.2	DWN		VIEW:	PART NO.:			
				4 < L ≤ 16	±0.3	CHKD		UNIT: mm/in	DWG NO.:			
				16 < L ≤ 63	±0.4	APPD		SIZE: A4	U-E-M7SS-Y-4			
				L > 63	±0.5				WEIGHT	SHEET	REVISION	
DESCRIPTION				DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES					
REVISIONS							KE SI DA ELECTRONIC TECHNOLOGY CO., LTD					
WWW.BODONGKAIGUAN.NET				WWW.CKJACK.COM				WWW.KSDKG.COM				
											1/1	A0

