









RoHS
Compliant
2002/95/EC

Halogen Free

REV.	ECN.	NO.	APPD.



RECOMMENDED PCB LAYOUT



NOTES:

1. ELECTRICAL:

1) VOLTAGE CURRENT RATING: PIN1&5 1.8AMP MAX
/ PIN2&3&4 1AMP MAX. ,30V AC;

2) INSULATION RESISTANCE: 100MΩ MIN;

3) CONTACT RESISTANCE: 30mΩ MAX;

4) WITHSTANDING VOLTAGE: 100V AC; FOR 1 MIN.

5) OPERATING TEMPERATURE: -30°C TO +80°C.

2. Mechanical:

1) Mating Force: 35N MAX

2) Unmating Force: 10N MIN.

3. DIMENSIONS MARKED "▼" TO BE
CHECKED BY Q.C & IPQC.

4. PART NO.

1: Au 1U*
6: Au 30U*

T: TIN
N: NICKEL

W: WHITE
B: BLACK

1: PBT
2: PA6T
3: PA9T
4: LCP

Bill of materials:

NO	PARTS	MATERIAL	QTY	FINISHING	X. ±0.35	X.* ±2*	UNITS	mm	廣東科斯達電子科技有限公司			
3	SHELL	COPPER ALLOY	1	PLATED TIN	.X ±0.30	.X* ±1*	MAT'L	SEE NOTE	TITLE: MICRO USB B TYPE F 5P 牛角型全插4.45 8.6无柱			
2	HOUSING	LCP+30%GF	1	UL94V-0	.XX ±0.25	.XX*	SEE NOTE	SEE NOTE				
1	TERMINAL	COPPER ALLOY	5	PLATED GOLD	.XXX ±0.15	.XXX*	FINISH	SEE NOTE				
					THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ACCURATE INNOTECH INC AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ACCURATE INNOTECH INC				DR: Ricky 2018/9/5			
					Q'TY				CHKD: Ricky 2018/9/5			
					APPD:				SCALE: 5:1			
									SHEET: 1/1			
									REV: A			
									CUSTOMER DRAWING			