


Recommended PCB Layout  
Top View

Model N o.	PJ-242A-SMT	PJ-242B-SMT	PJ-242C-SMT	PJ-242D-SMT
Schematic				
PIN				
1	sleeve	sleeve	sleeve	sleeve
2	tip	tip	tip	tip
3	ring 1	ring 1	ring 1	ring 1
4	ring 2	ring 2	ring 2	ring 2
10	NP	tip switch	NP	tip switch
11	NP	NP	ring 1 switch	ring 1 switch



	MATERIAL	PLATING
terminal 1	Phosphor Bronze	Gold
terminal 2	Phosphor Bronze	Gold
terminal 3	Phosphor Bronze	Gold
terminal 4	Phosphor Bronze	Gold
terminal 10	Phosphor Bronze	Gold
terminal 11	Phosphor Bronze	Gold
plastic	High Temp. Thermoplastic	

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE: 2.5 PHONE JACK
$\Delta$ X					ANGULAR				PART NO.:
$\Delta$ X					X.X	$\pm 5^\circ$			
$\Delta$ X					X.XX	$\pm 0.2\text{mm}$			
					X.XXX	$\pm 0.1\text{mm}$			
						$\pm 0.05\text{mm}$			DWG NO.:
									PJ-242X-SMT
									WEIGHT
									1.0g
									SHEET
									1/1
									REVISION
									A0