



MODEL NO.	PJ-3020	PJ-3021	PJ-3022	PJ-3023
SCHEMATIC				

SPECIFICATION:

- RATING:DC30V 0.5A;
- CONTACT RESISTANCE: $\leq 50m\Omega$;
AFTER LIFE TEST: $\leq 100m\Omega$;
- INSULATION RESISTANCE: $\geq 100M\Omega$ (DC250V) ;
AFTER LIFE TEST: $\leq 50M\Omega$;
- WITHSTAND VOLTAGE:500V AC ;
- INSERTION AND EXTRACTION FORCE:3-30N;
- LIFE TEST:5,000 CYCLES Min.

	MATERIAL	PLATING
terminal 1	Phosphor Bronze	silver
terminal 2	Phosphor Bronze	silver
terminal 3	Phosphor Bronze	silver
terminal 4	Phosphor Bronze	silver
terminal 5	Phosphor Bronze	silver
terminal 6	Phosphor Bronze	silver
terminal 10	Phosphor Bronze	silver
plastic	High Temp. Thermoplastic	

MARK	DESCRIPTION	REVISIONS	DATE	REVISED	APPROVED	ANGULAR	$\pm 5^\circ$	DSND	DATE	SCALE: N/A	MODEL TYPE:		
ΔX						X.X	$\pm 0.2mm$	DWN	DATE	VIEW:	3.5 PHONE JACK		
ΔX						X.XX	$\pm 0.1mm$	CHKD	DATE	UNIT: mm	PART NO.:		
ΔX						X.XXX	$\pm 0.05mm$	APPD	DATE	SIZE: A4	DWG NO.:		
							UNSPECIFIED TOLERANCES				PJ-302X		
								Kosod Technology Co., Ltd.			WEIGHT	SHEET	REVISION
											1.0g	1/1	A0

www.bodongkaiguan.net

www.ksdkg.com