



**Specification:**

1. Rating : DC 30V 0.5A;
2. Contact resistance:  $\leq 30m\Omega$  ;  
After life test:  $\leq 50m\Omega$
3. Insulation resistance:  $\geq 100M\Omega$  (500VDC) ;  
After life test:  $\geq 50M\Omega$
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3N - 25N;
6. life test: 5000cycles min;
7. Operation temperature range: 20 °C - 70°C
8. Preservative temperature range: -10 °C - 85°C
9. Sign ▲ "is importance dimension

**Matching Plug**



	MATERIAL	PLATING
terminal 1	copper all oy	silver
terminal 2	copper all oy	silver
terminal 3	copper all oy	silver
terminal 4	copper all oy	silver
plastic	PA9T	

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	3.5 PHONE JACK
CHKD	DATE	UNIT: mm	PART NO.:
APPD	DATE	SIZE: A4	DWG NO.: PJ-315X
			WEIGHT
			SHEET
			REVISION

MARK	DESCRIPTION	DATE	REVISED	APPROVED	ANGLAR	±5°
Δ X					$L \leq 4$	±0.2
Δ X					$4 < L \leq 16$	±0.3
Δ X					$16 < L \leq 63$	±0.4
					$L > 63$	±0.5
						UNSPECIFIED TOLERANCES