


1. Rating : DC 30V 0.5A;
2. Contact resistance: $\leq 0.03\Omega$;
3. Insulation resistance: $\geq 100M\Omega$ (DC250V);
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-20N;
6. Life test: 5,000 cycles.



	MATERIAL	PLATING
terminal 3	Phosphor Bronze	tin
terminal 4	Phosphor Bronze	tin
terminal 5	Phosphor Bronze	tin
plastic	Pbt	

					ANGULAR	$\pm 5^\circ$	DSND		DATE		SCALE: N/A	MODEL TYPE: 3.5 PHONE JACK		
Δx					X.X	$\pm 0.2mm$	DWN		DATE		VIEW:	PART NO.:		
Δx					X.XX	$\pm 0.1mm$	CHKD		DATE		UNIT: mm	DWG NO.: PJ-318-X		
Δx					X.XXX	$\pm 0.05mm$	APPD		DATE		SIZE: A4			
MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES		Kosod Technology Co., Ltd.					WEIGHT 1.0g	SHEET 1/1	REVISION A0
REVISIONS														
www.bodongkaiguan.net														