


Temperature -20~70 C
 Rated Load DC 30V 0.3A
 Contact Resistance <0.03Ω
 Insulation Resistance >100MΩ
 Withstand Voltage AC500V(50Hz)/min
 Actuating Force 2.2~30N
 Life 3000次

color B:Black W:White



	MATERIAL	PLATING
terminal 1	Phosphor Bronze	silver
terminal 2	Phosphor Bronze	silver
terminal 3	Phosphor Bronze	silver
terminal 4	Phosphor Bronze	silver
terminal 5	Phosphor Bronze	silver
plastic	Pbt	

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
△X					ANGULAR ±5°
△x					X.X ±0.2mm
△x					X.XX ±0.1mm
					X.XXX ±0.05mm

DSND		DATE		SCALE: N/A	MODEL TYPE: 3.5 PHONE JACK
DWN		DATE		VIEW:	PART NO.:
CHKD		DATE		UNIT: mm	DWG NO.: PJ-358H-X
APPD		DATE		SIZE: A4	WEIGHT 1.0g SHEET 1/1 REVISION A0

KOSOD TECHNOLOGY CO., LTD

REVISIONS
www.bodongkaiguan.net www.ksdkg.com