


Rating (max.) 1A DC 12V
 Contact Resistance 50 mΩ max.
 Insulation Resistance 100 MΩ min. 500 V DC
 Withstand Voltage. 500 V AC for 1 min.
 Operating Force 0.5 - 2.0 Kgf
 Terminal Strength 0.15 kgf for 10s?
 Actuator Strength N/A
 Solderability 255 ± 5 °C
 Reflow Soldering 255°C, 10s
 Operating Life with Load N/A
 Cold Test -35 °C for 96 hrs
 Heat Test 85 °C for 96 hrs
 Operating Life without Load
 5,000 cycles, 100 mΩ max. ?
 Humidity Test 40 °C, 90 to 95% RH for 96 hrs



CIRCUIT DIAGRAM

P.C.B. LAYOUT
TOP VIEW

For and on behalf of

MARK	DESCRIPTION	DATE	REVISED	APPROVED
Δ X				
Δ X				
Δ X				

REVISIONS *(Authorized Signatures)*

UNSPECIFIED TOLERANCES

THIS DOCUMENT IS THE PROPERTY OF CHENSHENG ELECTRONICS CO., LTD. NO PART THEREOF MAY BE REPRODUCED AND USED WITHOUT THE PRIOR WRITTEN CONSENT OF THE OWNER

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW: <input checked="" type="checkbox"/> C	3.5PHONE JACK
CHKD	DATE	UNIT: mm	PART NO.: PJ-3767
APPD	DATE	SIZE: A4	DWG NO.: PJ-3767
			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

KOSOD TECHNOLOGY CO., LTD