



- NOTES:
- 1.0 RATING
 - 1.1 TEMPERATURE: -25° c TO +75° c;
 - 2.1 INSULATION RESISTANCE: 100M AT 500V DC
 - 2.2 DIELECTRIC STRENGTH: AC 500V, 60Hz FOR 1MINUTE;
 - 3.0 MATERIALS
 - 3.1 HOUSING: THERMOPLASTIC;
 - 3.2 CONTACT: COPPER ALLOY
 - 4.0 INSERTION & EXTRACTION FORCE
 - 4.1 INSERTION & EXTRACTION: 1.0 TO 2.5kgf;
 - AFTER LIFE TEST: 0.3 TO 2.5 kgf;

	MATERIAL	PLATING
terminal 1	Phosphor Bronze	tin
terminal 2	Phosphor Bronze	tin
terminal 3	Phosphor Bronze	tin
terminal 4	Phosphor Bronze	tin
terminal 5	Phosphor Bronze	tin
terminal 6	Phosphor Bronze	tin
plastic	Pbt	

MARK	DESCRIPTION	DATE	REVISED	APPROVED	ANGLAR	±5°
△X					X.X	±0.2mm
△X					X.XX	±0.1mm
△X					X.XXX	±0.05mm
REVISIONS					UNSPECIFIED TOLERANCES	
www.bodongkaiguan.net www.ksdkg.com						

DSND		DATE		SCALE: N/A	MODEL TYPE: 3.5 PHONE JACK	
DWN		DATE		VIEW:	PART NO.:	
CHKD		DATE		UNIT: mm	DWG NO.:	
APPD		DATE		SIZE: A4	PJ-378B	
				WEIGHT	SHEET	REVISION
KOSOD TECHNOLOGY CO., LTD				1.0g	1/1	A0