



NOTE:
 Rating: DC 12V 50mA
 Operating Force: 200±100gf
 Lifetime: 10,000 Cycles

PAPT NO	L
SS-3235D-02-L1	2.0
SS-3235D-02-L2	3.0
SS-3235D-02-L3	4.0

ITEM	PAPT NAME	TER,NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	6	Brass (0.30t)	ag Plated		
④	Contact spring	1	Phosphor branze	ag Plated		
③	Base	1	Pa46	Black		
②	Cover	1	Sus	Natural		
①	Keystake	1	Pa46	Black		

MARK	DESCRIPTION	DATE	REVISED	APPROVED	ANGLAR	±5°
△ X					X.X	±0.2mm
△ X					X.XX	±0.1mm
△ X					X.XXX	±0.05mm

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	SLIDE SWITCH
CHKD	DATE <td>UNIT: mm</td> <td>PART NO.:</td>	UNIT: mm	PART NO.:
APPD	DATE <td>SIZE: A4</td> <td>DWG NO.:</td>	SIZE: A4	DWG NO.:
			SS-3235D-02-X
			WEIGHT
			1.0g
			SHEET
			1/1
			REVISION
			A0

KOSOD TECHNOLOGY CO., LTD

www.bodongkaiguan.net www.ksdkg.com