



NOTE:
 Rating: DC 12V 50mA
 Operating Force: 200±100gf
 Lifetime: 10,000 Cycles

| PAPT NO | L |
|----------------|-----|
| SS-3235D-03-L1 | 2.0 |
| SS-3235D-03-L2 | 3.0 |
| SS-3235D-03-L3 | 4.0 |
| | |
| | |

| ITEM | PAPT NAME | TER.NO | QTY | MATERIAL | FINISHING | REMARK |
|------|----------------|--------|-----|-----------------|-----------|--------|
| ⑤ | Terminal | --- | 3 | Brass (0.30t) | ag Plated | --- |
| ④ | Contact spring | --- | 1 | Phosphor branze | ag Plated | --- |
| ③ | Base | --- | 1 | Pa46 | Black | --- |
| ② | Cover | --- | 1 | Sus | Natural | --- |
| ① | Keystake | --- | 1 | Pa46 | Black | --- |

| MARK | DESCRIPTION | DATE | REVISED | APPROVED | UNSPECIFIED TOLERANCES |
|------|-------------|------|---------|----------|------------------------|
| ΔX | | | | | |
| ΔX | | | | | |
| ΔX | | | | | |
| | | | | | |

| DSND | DATE | SCALE: N/A | MODEL TYPE: |
|------|------|------------|------------------------|
| DWN | DATE | VIEW: | SLIDE SWITCH |
| CHKD | DATE | UNIT: mm | PART NO.: |
| APPD | DATE | SIZE: A4 | DWG NO.: SS-3235D-03-X |
| | | | WEIGHT |
| | | | SHEET |
| | | | REVISION |