



NOTE:
 Rating: DC 12V 50mA
 Operating Force: 200±100gf
 Lifetime: 10,000 Cycles

| PAPT NO | L |
|-------------|-----|
| SS-3235S-L1 | 2.0 |
| SS-3235S-L2 | 3.0 |
| SS-3235S-L3 | 4.0 |
| | |
| | |

| ITEM | PAPT NAME | TER.NO | QTY | MATERIAL | FINISHING | REMARK |
|------|----------------|--------|-----|-----------------|-----------|--------|
| 5 | Terminal | 6 | 1 | Brass (0.30t) | ag Plated | |
| 4 | Contact spring | 1 | 1 | Phosphor bronze | ag Plated | |
| 3 | Base | 1 | 1 | Pa46 | Black | |
| 2 | Cover | 1 | 1 | Sus | Natural | |
| 1 | Keystake | 1 | 1 | Pa46 | Black | |

| MARK | DESCRIPTION | DATE | REVISED | APPROVED | ANGLAR | ±5° | SCALE: N/A | MODEL TYPE: |
|------|-------------|------|---------|----------|--------|---------|------------|--------------|
| Δ x | | | | | X.X | ±0.2mm | VIEW: | SLIDE SWITCH |
| Δ x | | | | | X.XX | ±0.1mm | UNIT: mm | PART NO.: |
| Δ x | | | | | X.XXX | ±0.05mm | SIZE: A4 | DWG NO.: |
| | | | | | | | | SS-3235S-X |
| | | | | | | | | WEIGHT |
| | | | | | | | | 1.0g |
| | | | | | | | | SHEET |
| | | | | | | | | 1/1 |
| | | | | | | | | REVISION |
| | | | | | | | | A0 |