


SPECIFICATION

Contact Rating : 50mA, 12V DC
 Contact Resistance : 100mΩ max
 Insulation Resistance : 100mΩ min. 500V DC
 Dielectric Strength : 250V AC/1minute
 Travel : 0.25mm
 Operating Temp : -20°C ~ +70°C
 Storage Temp : -30°C ~ +80°C

PAPT NO	TC-1101T-X-X-X
Operating Force	A: 100gf B: 160gf C: 260gf
Height	A: H: 4.3 B: H: 5.0
Yellow	B: Black W: White

P.C.B MOUNTING HOLES



⑤	Terminal	—	2	Brass (0.30t)	Plating silvering	—
④	Contact	—	1	F.ag/Sus	Natural	—
③	Base	—	1	LCP	—	—
②	Cover	—	1	Spcc	Plating Nickel	—
①	Keyslake	—	1	Pa46	—	—
ITEM	PAPT NAMF	TER.NO	QTY	MATERIAL	FINISHING	REMARK

					units: mm	DSND		DATE		SCALE: N/A	MODEL TYPE:
					tolerance:	DWN		DATE		VIEW:	TACT SWITCH
					X.X ±0.2mm	CHKD		DATE		UNIT: mm	PART NO.:
					X.XX ±0.1mm	APPD		DATE		SIZE: A4	DWG NO.:
					X.XXX ±0.05mm						TC-1101T-X-X-X
MARK					UNSPECIFIED TOLERANCES	KOSOD TECHNOLOGY CO., LTD					WEIGHT
REVISIONS										1.0g	
www.bodongkaiguan.net www.ksdkg.com										SHEET	
										1/1	
										REVISION	
										A0	