



NOTE:
 1. Rating : DC 5V 10mA
 2. Contact Resistance: 100mΩMAX
 3. Insulation Resistance: 100MΩMIN
 4. Soldering Temper: 260±5°/5s
 5. Mechanical Life: 100,000 cycles
 6. Ever Portion 80 ± 50 gf
 7. Push Portion 205 ± 80 gf
 8. Travel: -24° 0° +24°

ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	5	5	Phosphor Bronze	Plating silver	
④	Base	1	1	Lcp		
③	Spring	1	1	Sus	Natural	
②	Cover	1	1	Sus	Natural	
①	Keystake	1	1	Ppa		

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE: MULTI-FUNCTIONAL SWITCH
△X					ANGULAR ±5°	DWN	DATE	VIEW:	PART NO.:
△X					X.X ±0.2mm	CHKD	DATE	UNIT: mm	DWG NO.:
△X					X.XX ±0.1mm	APPD	DATE	SIZE: A4	TM-2011A
					X.XXX ±0.05mm				WEIGHT 1.0g
									SHEET 1/1
									REVISION A0

www.bodongkaiguan.net www.ksdkg.com

KOSOD TECHNOLOGY CO., LTD