


Circuit Diagram



Detail of P (SCALE: 2:1)

NOTE:
 Rating: DC 30V 0.1A
 Operating Force: 40±10gf
 Lifetime: 100,000 Cycles

PART NO.	H
TM-T07A-1	8.3
TM-T07A-2	8.5
TM-T07A-3	8.7
TM-T07A-4	9.3
TM-T07A-5	11.0
TM-T07A-6	12.3
TM-T07A-7	13.7

⑤	Contact Spring	—	1	Phosphor Bronze	Plating silver	—
④	Terminal	—	4	Phosphor Bronze	Plating silver	—
③	Base	—	1	Nylon		—
②	Cover	—	1	Nylon		—
①	Keystake	—	1	Nylon		—
ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK

					ANGLAR	±5°	DSND	DATE	SCALE: N/A	MODEL TYPE:		
△x					X.X	±0.2mm	DWN	DATE	VIEW:	DETECT SWITCH		
△x					X.XX	±0.1mm	CHKD	DATE	UNIT: mm	PART NO.:		
△x					X.XXX	±0.05mm	APPD	DATE	SIZE: A4	DWG NO.:		
MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES			KOSOD TECHNOLOGY CO., LTD			DWG NO.:	
www.bodongkaiguan.net www.ksdkg.com										TM-T07A-X		
										WEIGHT	SHEET	REVISION
										1.0g	1/1	A0