



NOTE:
 Rating: DC 30V 0.1A
 Operating Force: 40 ± 10 gf
 Lifetime: 100,000 Cycles

PART NO.	H
TM-W07A-1	8.3
TM-W07A-2	8.5
TM-W07A-3	8.7
TM-W07A-4	9.3
TM-W07A-5	11.0
TM-W07A-6	12.3
TM-W07A-7	13.7

ITEM	PAPT NAMF	TER.NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Contact Spring	—	1	Phosphor Bronze	Plating silver	—
④	Terminal	—	4	Phosphor Bronze	Plating silver	—
③	Base	—	1	Nylon	—	—
②	Cover	—	1	Nylon	—	—
①	Keystake	—	1	Nylon	—	—

MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE: DETECT SWITCH		
△X					ANGULAR X.X ±0.2mm	DWN	DATE	VIEW:	PART NO.:		
△X					X.XX ±0.1mm	CHKD	DATE	UNIT: mm	DWG NO.:		
△X					X.XXX ±0.05mm	APPD	DATE	SIZE: A4	TM-W07A-X		
www.bodongkaiguan.net www.ksdkg.com						KOSOD TECHNOLOGY CO., LTD			WEIGHT 1.0g	SHEET 1/1	REVISION A0