



CIRCUIT DIAGRAM

SPECIFICATION

Contact Rating: 50mA,12V DC
 Contact Resistance: 100mΩ max
 Insulation Resistance: 100mΩ
 min.500V DC
 Dielectric Strength: 250V
 AC/1minute
 Travel: 0.20mm
 Operating Temp: -30℃~+85℃
 Storage Temp: -30℃~+80℃

PAPT NO	TS-1133-X-B
Operating Force	A:100gf B:160gf C:260gf
Keystake	A:PA46: B:Silica gel

⑤	Terminal	—	3	Brass (0.30t)	Plating silvering	—
④	Contact	—	1	F.ag/Sus	Natural	—
③	Base	—	1	Pa46	—	—
②	Cover	—	1	Spcc	Plating Nickel	—
①	Keystake	—	1	Silica gel	—	—
ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK

PCB. WELDING DRAWING

DSND		DATE		SCALE: N/A	MODEL TYPE: TACT SWITCH		
DWN		DATE		VIEW:	PART NO.:		
CHKD		DATE		UNIT: mm	DWG NO.:		
APPD		DATE		SIZE: A4	TS-1133-X-B		
UNSPECIFIED TOLERANCES					WEIGHT	SHEET	REVISION
www.bodongkaiguan.net www.ksdkg.com					1.0g	1/1	A0

KOSOD TECHNOLOGY CO., LTD

units: mm
 tolerance:
 X.X ±0.2mm
 X.XX ±0.1mm
 X.XXX ±0.05mm

MARK	DESCRIPTION	DATE	REVISED	APPROVED