



SPECIFICATION

Contact Rating : 50mA,12V DC
 Contact Resistance : 100mΩ max
 Insulation Resistance : 100mΩ min.500V DC
 Dielectric Strength : 250V AC/1minute
 Travel : 0.20mm
 Operating Temp : -30℃~+85℃
 Storage Temp : -30℃~+80℃

PAPT NO	TS-1145-X-B
Operating Force	A: 100gf B: 160gf C: 260gf
Height	H: 2.5
Keystake	A: PA46: B: Silica gel

CIRCUIT DIAGRAM

P.C.B MOUNTING HOLES

PACKING REEL TYPE 3,000/1REEL(EA)

⑤	Terminal	—	4	Brass (0.30t)	Plating silvering	—
④	Contact	—	1	F.ag/Sus	Natural	—
③	Base	—	1	Lcp		—
②	Cover	—	1	Brass	Plating Nickel	—
①	Keystake	—	1	Silica gel		—
ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK

				units: mm	DSND	DATE	SCALE: N/A	MODEL TYPE:		
				tolerance:	DWN	DATE	VIEW:	TACT SWITCH		
ΔX				X.X ±0.2mm	CHKD	DATE	UNIT: mm	PART NO.:		
ΔX				X.XX ±0.1mm	APPD	DATE	SIZE: A4	DWG NO.:		
ΔX				X.XXX ±0.05mm				TS-1145-X-B		
MARK	DESCRIPTION	DATE	REVISED	APPROVED				WEIGHT	SHEET	REVISION
	REVISIONS				UNSPECIFIED TOLERANCES			1.0g	1/1	A0
www.bodongkaiguan.net www.ksdkg.com							KOSOD TECHNOLOGY CO., LTD			