



SPECIFICATION

Contact Rating : 50mA,12V DC
 Contact Resistance : 100mΩ max
 Insulation Resistance : 100mΩ min.500V DC
 Dielectric Strength : 250V AC/1minute
 Travel : 0.20mm
 Operating Temp : -30 °C~+85 °C
 Storage Temp : -30 °C~+80 °C

CIRCUIT DIAGRAM



P.C.B MOUNTING HOLES



PACKING REEL TYPE

4,000/1 REEL (EA)

PAPT NO	TS-1145A-X-X
Operating Force	A: 100gf B: 160gf C: 260gf
Height	H: 2.5
Keystone	A: PA46: B: Silica gel

⑤	Terminal	—	4	Brass (0.30t)	Plating silvering	—
④	Contact	—	1	F.ag/Sus	Natural	—
③	Base	—	1	Lcp	—	—
②	Cover	—	1	Brass	Plating Nickel	—
①	Keystone	—	1	Pa46	—	—
ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK

					units: mm	DSND		DATE		SCALE: N/A	MODEL TYPE:		
					tolerance:	DWN		DATE		VIEW:	TACT SWITCH		
					X.X	CHKD		DATE		UNIT: mm	PART NO.:		
					X.XX	APPD		DATE		SIZE: A4	DWG NO.:		
					X.XXX						TS-1145A-X-X		
					UNSPECIFIED TOLERANCES	Kosod Technology Co., Ltd.					WEIGHT	SHEET	REVISION
											1.0g	1/1	A0
MARK	DESCRIPTION	DATE	REVISED	APPROVED									
REVISIONS													
www.bodongkaiguan.net		www.ksdkg.com											