




PCB LAYOUT(X0.5)

SPECIFICATION

Contact Rating: 50mA,12V DC
 Contact Resistance: 100mΩ max
 Insulation Resistance: 100mΩ min.500V DC
 Dielectric Strength: 250V AC/1minute
 Travel: 0.20mm
 Operating Temp: -30°C~+85°C
 Storage Temp: -30°C~+80°C



CIRCUIT DIAGRAM

PAPT NO	TS-1824SR-X
Operating Force	B:160gf C:260gf
Height	H:0.55

ITEM	PAPT NAME	TER.NO	QTY	MATERIAL	FINISHING	REMARK
⑤	Terminal	—	4	Brass (0.30t)	Plating silvering	—
④	Contact	—	1	F.ag/Sus	Natural	—
③	Base	—	1	Lcp		—
②	Cover	—	1	kapton filmPI	Plating Nickel	—
①	Keystake	—	1			—

REVISIONS					UNSPECIFIED TOLERANCES	DSND	DATE	SCALE: N/A	MODEL TYPE:		
Δx					units: mm	DWN	DATE	VIEW:	TACT SWITCH		
Δx					tolerance:	CHKD	DATE	UNIT: mm	PART NO.:		
Δx					X.X ±0.2mm	APPD	DATE	SIZE: A4	DWG NO.:		
MARK	DESCRIPTION	DATE	REVISED	APPROVED	X.XX ±0.1mm				TS-1824SR-X		
					X.XXX ±0.05mm				WEIGHT	SHEET	REVISION
www.bodongkaiguan.net www.ksdkg.com						KOSOD TECHNOLOGY CO., LTD			1.0g	1/1	A0