






Pin #	SIGNAL NAME	DESCRIPTION	MATING SEQUENCE
1	VBUS	POWER	SECOND
2	D-	USB 2.0 DIFFERENTIAL PAIR	THIRD
3	D+		
4	GND	GROUND FOR POWER RETURN	SECOND
5	S_H_SSR(L)	SUPER SPEED RECEIVER DIFFERENTIAL PAIR	LAST
6	S_H_SSR(R)		
7	GND_DRN	GROUND FOR SIGNAL RETURN	
8	S_H_SST(L)	SUPER SPEED TRANSMITTER DIFFERENTIAL PAIR	
9	S_H_SST(R)		
Shell	Shell	CONNECTOR METAL SHELL	FIRST



Material
Housing Material: LCP, UL94V-0, blue
Contact Terminal: Brass
Metallic Shell: Brass
Plating
Underplating: Nickel
Contact Plating: 1µ" Gold
Solder Tail: 100µ" Min. Tin
Metallic Shell: Nickel

Electrical
Voltage Rating: 100 V AC
Current Rating: 0.25A (Signal pins 2,3,5,6,7,8,9) 1.8A (Power Pins 1,4)
Contact Resistance: 30mΩ Max.
Insulation resistance: 1000MΩ Min.
Dielectric withstanding voltage: 100V AC/Minute

Mechanical
Durability: 1500 cycles
Mating Force: 35N (3.57Kgf) Max
Unmating Force: 10N (1.02Kgf) Min. initial, 8N min after test
Environmental and Processing
Operating Temperature: -40°C to +85°C



MARK	DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
ΔX					ANGLAR ±5°
ΔX					L ≤ 4 ±0.2
ΔX					4 < L ≤ 16 ±0.3
					16 < L ≤ 63 ±0.4
					L > 63 ±0.5

DSND	DATE	SCALE: N/A	MODEL TYPE: USB 3.0
DWN	DATE	VIEW:	PART NO.:
CHKD	DATE	UNIT: mm	DWG NO.:
APPD	DATE	SIZE: A4	U235-09XN-4BLRC16-X-5
			WEIGHT 1.0g
			SHEET 1/1
			REVISION A0

KOSOD TECHNOLOGY CO., LTD

REVISIONS
www.bodongkaiguan.net www.ksdkg.com