


RECOMMENDED P.C.B LAYOUT(TOP VIEW)
GENERAL TOLERANCE ± 0.05



NOTE:

1. ELECTRICAL CHARACTERISTICS
 - 1-1. CONTACT RESISTANCE:
80 milliohms MAX.
 - 1-2. INSULATION RESISTANCE:
1,000 Megohms MIN.
 - 1-3. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.
2. MECHANICAL CHARACTERISTICS
RETENTION FORCE:MIN.100gf/PIN
3. RoHS 2002/95/EC COMPLIANT.

ITEM	PAPT NAMF	QTY	MATERIAL	FINISHING
③	PEG	1	COPPER ALLOY	
②	Terminal	8	COPPER ALLOY	
①	Housing	1	HI-TEMP.PLASIC UL 94V-0	BLACK

MARK	DESCRIPTION	DATE	REVISED	APPROVED	ANGULAR	TOLERANCES
					$L \leq 4$	$\pm 5^\circ$ ± 0.2
Δ					$4 < L \leq 16$	± 0.3
Δ					$16 < L \leq 63$	± 0.4
					$L > 63$	± 0.5
					UNSPECIFIED TOLERANCES	

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	TF CARD CONN
CHKD	DATE	UNIT: mm	PART NO.:
APPD	DATE	SIZE: A4	DWG NO.: XKTF-004
KOSOD TECHNOLOGY CO., LTD			WEIGHT: 1.0g
			SHEET: 1/1
			REVISION: A0